



Technical Data

Mounted on KOMATSU PC 75 excavator base

Rotary:

Nominal torque	35 KNm	25,800 lbsft
Max nominal pulldown	30 KN	6,750 lbs
Max nominal pullback	40 KN	9,000 lbs
Unloading speed	84 rpm	
Rotary stroke	950 mm	3.11 ft

Winches:

Main winch nominal pullback	36 KN	8,100 lbs
Auxiliary winch nominal pullback	10 KN	2,250 lbs

Diesel Engine:

KOMATSU 4D98E-2XFB

Power	50 KW 2.300 rpm	67 HP @ 2,300 rpm
Hydraulic Installation	2 pumps	
Hydraulic oil tank	70 liters	18.48 gal
Fuel Tank	100 liters	26.4 gal

Crawler:

Length	2.875 mm	9.5 ft
Width	2.050 mm	6.7 ft
Shoes	450 mm	1.5 ft

Approx. Weight:	11,2 tons	24,685 lbs
------------------------	-----------	------------

MAIT S.p.A. DRILLING RIGS
 via Flaminia Seconda, 149/153 - P.O. Box 1040 60027 OSIMO (AN) ITALY
 - TEL +39 071 7822186 - FAX +39 071 780535
 - web: <http://www.mait.it> - E-mail: info@mait.it

